

# DATA SHEET

## FINISH DSV GLOSS, SATIN, MATT

FINISH DSV is a two-component aliphatic solvent-based polyurethane paint, which guarantees high resistance to abrasion and chemical agents.

Specially developed for the protection of RECRYTE READYDECOR

Colorless in nature, it does not yellow under the action of sunlight. It can be applied outside and inside.

### FORMAT

Component A - 4L

Component B - 2 x 1L

### PRODUCT CODES

FINISH DSV GLOSS (A + B) RE5006

FINISH DSV MATT (A + B) RE5007

FINISH DSV SATIN (A + B) RE5008

### SPECIFICATIONS

Application temperature: Between 10 ° and 25 ° C

Ambient humidity: less than 90%

PERSOZ HARDNESS (20 ° C)

4h	12h	24h	7 DAYS	30 DAYS	total
60''	110''	140''	185''	233''	246'

RESISTENZA A PRODOTTI PER L'IGIENE DOMESTICA

SATIN	WATER	ALCOHOL	AMMONIA 3%	BLEACH 4%	SALFUMAN 24%
1H	Not affect	Not affect	Not affect	Not affect	Not affect
4H	Not affect	lightly	Not affect	Not affect	Not affect
24H	Not affect	lightly	Not affect	Not affect	lightly

MATT	WATER	ALCOHOL	AMMONIA 3%	BLEACH 4%	SALFUMAN 24%
1H	Not affect	Not affect	Not affect	Not affect	Not affect
4H	Not affect	lightly	Not affect	Not affect	Not affect
24H	Not affect	lightly	Not affect	Not affect	lightly

### INSTRUCTIONS FOR USE RECRYTE FINISH DSV



It is applied with a roller

1. Mix and homogenize the product by hand or machine at low speed. (2 parts A + 1 part B).
2. The surface must be dry, free of grease and contaminants.
3. On concrete the surface must be completely set (28 days) and free of moisture
4. The number of layers (2-4) will depend on the absorption of the substrate; On very porous surfaces, a greater number of layers is necessary to avoid the differences in gloss due to the different absorption of the binder in the substrate.
5. The substrate temperature must be above 10 ° C and at least 3 ° C above the dew point.
6. The drying time of the different layers is 4-6 hours depending on the weather conditions.

### **STORAGE INSTRUCTIONS**

RECRYTE FINISH DSV must be stored in its original container tightly closed and protected from bad weather. Always store in cool places and do not leave exposed to the sun, at a temperature between 5 and 25 ° C during storage. Usage time is 12 months from the production date, properly stored.

### **HYGIENE AND SAFETY**

Use in well-ventilated areas with personal protective equipment. Keep out of reach of children.

### **DISPOSAL AND ENVIRONMENT**

Do not dispose of waste in sewers or water courses. Empty containers must be disposed of in accordance with local / national legislation in force

