

# DATA SHEET

## PRIMER UNION

RECRYTE PRIMER UNION is a water-based acrylic resin used as an adhesion promoter between low porosity or non-porous surfaces, old surfaces and new coatings.

Guarantees maximum adhesiveness and elasticity to the decorative coating.

PRIMER UNION is used with the READYDECOR, MIPOX and READYCORK systems

### COMPOSITION

Acrylic resin

### FORMAT

5L

### PRODUCT CODE

RE1002

### SPECIFICATIONS

- o Appearance: white liquid
- o Density:  $\pm 0.04$  gr / cm<sup>3</sup>
- o Application temperature: from +0 ° C to +30 ° C
- o Toxicity / Flammability: no

### INSTRUCTIONS FOR USE READYDECOR PRIMER UNION

It is applied with a brush or roller

1. Apply to clean, dry surfaces free from dust, grease and mold. Old paints must be scratched and cleaned thoroughly to ensure perfect adhesion of the product.
2. Apply one coat with a short pile polyester roller. Allow the adhesion promoter to dry at least one hour before applying the coating

Yield: 0.10 L / m<sup>2</sup> depending on the absorption of the substrate.

### HYGIENE AND SAFETY

- Use in well ventilated areas with personal protective equipment.
- Keep out of reach of children.

### STORAGE INSTRUCTIONS

- Protect containers from extreme temperatures, direct sun exposure and frost, at temperatures between 5 ° and 25 ° during storage
- Usage time is 6 months from production date, properly stored.

### DISPOSAL AND ENVIRONMENT

- Do not dispose of waste in sewers or water courses.
- Empty containers must be disposed of in accordance with local / national legislation in force

